



ANCHORSEAL® 2 is a hybrid of plant-based polymers and wax that protects the ends of green logs and lumber from checking and splitting.

ANCHORSEAL 2 controls the rate of moisture loss during air drying for hardwood, exotic hardwood decking and softwood. ANCHORSEAL 2 should be applied immediately after cutting for best results in preventing costly degradation.

FEATURES

- Prevents up to 90% of end checks and drying splits
- Prevents end checking in tropical hardwood deck boards
- Improves yield with less waste
- Easily applied using a brush, roller or sprayer
- Water based, non-hazardous, non-toxic formula
- Soap and water cleanup
- Available in summer and winter formulas
- Available in clear or more than 35 colors

GREAT FOR USE ON

- Hardwood logs and lumber
- Softwood timbers and lumber
- Tropical hardwood lumber
- Ipe decking
- Woodturning blanks
- Log “cookies”
- Live-edge wood slabs



For more information, visit www.uccoatings.com.

U·C COATINGS
WOOD PROTECTION PRODUCTS

Manufactured by U·C Coatings, LLC
2250 Fillmore Avenue, Buffalo, NY 14214

716-833-9366 | toll free: 1-888-363-2628 | sales@uccoatings.com



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

ANCHORSEAL 2® combines our wax emulsion with natural, plant-based polymers to create a hybrid end sealer that protects freshly cut logs and lumber from damaging end checks and splits while air drying. ANCHORSEAL 2 can be used on hardwood and softwood logs and lumber to protect against costly degradation.

FEATURES

- Prevents up to 90% of end checks and drying splits
- Hybrid formula combines wax with natural plant-based polymers
- Can be applied to all species of hardwood or softwood
- Helps prevent blue stain and sapstain caused by damaging fungi
- Water based, non-toxic formula
- Available in clear or more than 35 colors
- Winterized formulas available

PACKAGING SIZES

1 Quart Can | 1 Gallon Can | 5 Gallon Pail
55 Gallon Drum | 275 Gallon Tote

FREIGHT CLASS

55

TYPICAL PHYSICAL CHARACTERISTICS

Color	Viscous white liquid, dries translucent
pH	8-9
lbs/gal	8
Specific Gravity	0.95
Viscosity	4,000 cps
Application Temp.	50°F - 90°F (10°C - 32.2°C)
Odor	Nil

SURFACE PREPARATION

All areas to be coated should be clear of dirt and debris.

APPLICATION

- Apply a heavy film of ANCHORSEAL 2 using a brush, roller or sprayer until it begins to drip slightly.
- For optimal coverage, use a gas engine, electric, air operated or backpack sprayer from U-C Coatings.
- If using spray equipment other than those sold by U-C Coatings, use 0.21"/0.55 mm tip or larger.
- Logs larger than 24"/60 cm in diameter will require a heavier coating, or two coats must be applied within a 15 minute period.

COVERAGE

- 100 sq. ft./gallon, depending on application method and wood species.

CLEANUP & STORAGE

- Clean application equipment using hot soapy water.
- Store unused ANCHORSEAL 2 above 50°F/10°C to prevent freezing. Winterized formulas will protect against freeze damage.

PRECAUTIONS

- Contains no toxic or hazardous materials
- Safety Precautions
 - Wear vinyl gloves and eye protection.
 - Avoid breathing in spray. If inhaled, move to fresh air.
 - Avoid contact with eyes. If splashed into eyes, rinse with clean water for 15 minutes.
 - If skin irritation occurs, wash area with soap and water.
 - If accidentally ingested, immediately drink 2 glasses of water and contact a physician. Do not induce vomiting.
 - In case of accidental overexposure, seek medical help.

U·C COATINGS
WOOD PROTECTION PRODUCTS

Manufactured by U-C Coatings, LLC
P.O. Box 1066 | Buffalo, NY 14215 USA
(716) 833-9366 | sales@uccoatings.com | www.uccoatings.com

"ANCHORSEAL 2" is a registered trademark of U-C Coatings, LLC.